





Signal Microwave FPP Probe Series

40/50/70/110 GHz Wide Pitch True Differential TDR/VNA Probes

Signal Microwave, in partnership with DVT Solutions, is producing a series of differential probes. The DVT-FPPXX, are 40 GHz, 50 GHz, 70 GHz, and 110 GHz true differential probes. These probes are designed to support the industry's demand for higher data rates over differential traces. They are used to characterize transmission lines and devices such as 28 - 56 GHz Nyquist bandwidth 5-parameters for standards like PCle6 with SerDes technology.

To meet these needs, a newly patented differential probe design was developed to replace internal cable wires with a printed circuit board. It has a high bandwidth differential transmission line that can be used with test equipment to measure differential S-parameters up to 110 GHz. There are also de-embedding methods and boards available that support the probes.

- · 100 ohm true odd mode differential
- 2 signal pins only no ground pins
- Multiple bandwidths
 - 40 GHz. 50 GHz. 70 GHz. and 110 GHz
- Multiple probe pin pitches
 - 1.0 mm, 0.8 mm, and 0.6 mm pin pitches
- Multiple 3 hole mounting configurations
 PM-001: X-axis, y-axis, and up/down axis control
 PM-002: X-axis, y-axis, and theta angle axis control
- Straight 1 hole mounting
- Custom mounting configurations available
- . Multiple pin lengths available as options
- 1 year warranty

Signal Microwave, LLC

Tempe, Arizona info@signalmicrowave.com www.signalmicrowave.com (480) 322-4992

Probe 70 GHz s-parameters



